

Representative Image

Catalog No. K655LRTPN0330DRG

Description: 600 AMP DB STICK-OP CONNECTOR KIT

UPC No 783786844869

Home > Medium Voltage Utility Solutions > Elastimold > Electrical connector assembly

600 Amp, 25kV, Stick-Op Connector Kit with Insulated Cap. Aluminum Compression Lug. Cable Insulation Diameter 1.515 inch to 1.780 inch. Conductor Size AWG or kcmil, Compressed Stranded 500 /Compacted Solid 600 /mmSquared Compact 250/300.

Descriptors

Category	Electrical connector assembly
Special Features	Reducing Tap Plug 600 to 200 Amps. Provides an External Visible Break by Hotstick Removal of the Elbow.
Application	Connect 600 Amp interface to 200 Amp Loadbreak Tap

Specifications

Conductor Range	500 kcmil , 600 kcmil
Material	Housing - EPDM Rubber
Color	Black
Enclosure	Yes, EPDM Rubber
Voltage Rating	25 kV
Amperage Rating	600 to 200 A
Insulation	Yes, EPDM Rubber
Temperature Rating	-40 to +65 C
Environmental Conditions	All Weather Conditions

Classifications

Brand Name	Elastimold
Standard	ANSI/IEEE Standard 386