XLPE URD Power Service 4C

4x16mm2 0.6/1.0kV XLPE URD to Vic Spec



4 core Low Voltage Underground Residential Distribution Cable to AS/NZS 4026. Manufactured to PVC Best Practice Guidelines.

STANDARDS

Product AS/NZS 4026

- Plain Annealed Copper conductors
- 0.6/1kV
- X-90 insulated (Colours: Red, White, Blue, Black)
- PVC sheathed
- Low Voltage Underground Residential Distribution Cable to AS/NZS 4026, 90°C.

Nexans
Ref.: HEVP15SJ004CXEM

Country
Ref.: HEVP15SJ004CXEM

EAN 13: 99319215298220

CONTACT

Internal Sales
Phone: 1300 CABLES
olex.csquotes@nexans.com

Conductor flexibility
Class 2

Rated Voltage Uo/U (Um)
0,6/1 kV

Cable flexibility
Rigid

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

XLPE URD Power Service 4C

4x16mm2 0.6/1.0kV XLPE URD to Vic Spec

CHARACTERISTICS

Construction characteristics	
Colour	Black
Conductor flexibility	Class 2
Conductor material	Copper
Conductor shape	Circular
Insulation	X-90
Insulation colour	Red, black, white, blue
Outer sheath	PVC
Type of conductor	Copper
With Green/Yellow core	No
With smaller neutral conductor	No
Dimensional characteristics	
Approximate weight	77.0 kg/100m
Cable length	500 m
Conductor cross-section	16 mm²
Diameter over insulation	7.9 mm
Neutral conductor section (when smaller)	- mm²
Nominal insulation thickness	1.5 mm
Nominal overall diameter	22.1 mm
Number of cores	4
Electrical characteristics	
Conductor AC resistance at 50 Hz	1.47 Ohm/km
Inductive reactance at 50Hz	0.074 Ohm/km
Insulation resistance at 20°C	860 MOhm.km
Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Rated Voltage Uo/U (Um)	0,6/1 kV
Mechanical characteristics	
Cable flexibility	Rigid

ENVIRONMENTAL DATA

Global Carbon Footprint	
Amount of CO_2 emitted Cradle to Gate phase (raw material collection and manufacturing), for the production of 1 km of cable.	**3.82 t eq. CO_2**

Environmental information coming from Nexans' Product Environmental Profile (PEP Ecopassport®)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.